



Ablux

Technical data

SolidCORE Living

Cover type	
According to MMFA:	2
Plank format (L x B):	1,220 mm x 181 mm
Thickness of element:	4.5 mm
Wear layer:	0.3 mm
Utilisation class:	23/31
Weight:	7.3 kg/m ²
Installation:	floating
Locking system:	L2C
Dimension stability:	0.01 % across
Slip resistance level:	R10
Fire behaviour:	Bfl - S1
Footfall sound absorption:	20 dB
Thermal transmittance:	0.031 (m ² K)W
Thermal conductivity:	0.145 W/(mK)
Underfloor heating:	suitable for installation on warm water underfloor heating
Packaging units:	1 pack = 14 planks = 3.09 m ² 1 pal. = 40 pack = 123.66 m ²

SolidCORE X-treme

Cover type	
According to MMFA:	2
Plank format (L x B):	1,220 mm x 181 mm
Thickness of element:	5.5 mm
Wear layer:	0.5 mm
Utilisation class:	33/42*
Weight:	9.4 kg/m ²
Installation:	floating
Locking system:	DropDown System
Dimension stability:	0.01 % across
Slip resistance level:	R10
Fire behaviour:	Bfl - S1
Footfall sound absorption:	20 dB
Thermal transmittance:	0.038 (m ² K)W
Thermal conductivity:	0.145 W/(mK)
Underfloor heating:	suitable for installation on warm water underfloor heating
Packaging units:	1 pack = 10 planks = 2.208 m ² 1 pal. = 50 pack = 110.41 m ²

SolidCORE X-clusive

Cover type	
According to MMFA:	2
Plank format (L x B):	1,800 mm x 225 mm
Thickness of element:	5.5 mm
Wear layer:	0.5 mm
Utilisation class:	33/42*
Weight:	9.4 kg/m ²
Installation:	floating
Locking system:	DropDown System
Dimension stability:	0.01 % across
Slip resistance level:	R10
Fire behaviour:	Bfl - S1
Footfall sound absorption:	20 dB
Thermal transmittance:	0.038 (m ² K)W
Thermal conductivity:	0.145 W/(mK)
Underfloor heating:	suitable for installation on warm water underfloor heating
Packaging units:	1 pack = 6 planks = 2.43 m ² 1 pal. = 39 pack = 94.77 m ²

SolidCORE Brick-Design

Cover type	
According to MMFA:	2
Plank format (L x B):	940 mm x 470 mm
Thickness of element:	5.5 mm
Wear layer:	0.5 mm
Utilisation class:	33/42*
Weight:	9.4 kg/m ²
Installation:	floating
Locking system:	DropDown System
Dimension stability:	0.01 % across
Slip resistance level:	R10
Fire behaviour:	Bfl - S1
Footfall sound absorption:	20 dB
Thermal transmittance:	0.038 (m ² K)W
Thermal conductivity:	0.145 W/(mK)
Underfloor heating:	suitable for installation on warm water underfloor heating
Packaging units:	1 pack = 5 planks = 2.209 m ² 1 pal. = 45 pack = 99.405 m ²

SolidCORE X-cellent

Cover type	
According to MMFA:	2
Plank format (L x B):	1,220 mm x 225 mm
Thickness of element:	5.5 mm
Wear layer:	0.5 mm
Utilisation class:	33/42*
Weight:	9.3 kg/m ²
Installation:	floating
Locking system:	DropDown System
Dimension stability:	0.01 % across
Slip resistance level:	R10
Fire behaviour:	Bfl - S1
Footfall sound absorption:	20 dB
Thermal transmittance:	0.038 (m ² K)W
Thermal conductivity:	0.145 W/(mK)
Underfloor heating:	suitable for installation on warm water underfloor heating
Packaging units:	1 pack = 8 planks = 2.196 m ² 1 pal. = 48 pack = 105.408 m ²

MATECTA®Premium

MATECTA® podstawowe zalety:

1. Bardzo matowa, naturalna powierzchnia, Synchron
2. Poziom połysku 3-5 - Jeszcze bardziej odporny na zarysowania dzięki zastosowaniu PU z cząsteczkami ceramicznymi
4. Bardzo łatwa konserwacja - brud słabo przylega
5. Większa odporność na poślizg

Wraz z wprowadzeniem nowej ochrony powierzchni MATECTA® Premium, kolekcja Brick-Design ma teraz neutralny pod względem emisji CO2 karton o świeżym designie.

Ablux10-2020-SolidCore-250-1-EN
Zachowanie elektrostatyczne zgodnie z EN1815:2016 dotyczących wszystkich pokryć 0,1KV
Błędy i zmiany techniczne zastrzeżone. Stan 07/2020



Ablux

ABLUX
ul. Jana Henryka Dąbrowskiego 6
87-100 Toruń